

最大续驶里程 (km) : 650

Top  
81



中国航天科工集团第九研究院

China Aerospace Science and Industry Cooperation 9<sup>th</sup> Academy





最大续驶里程 (km) : 650

Top 81



中国航天科工集团第九研究院

China Aerospace Science and Industry Cooperation 9<sup>th</sup> Academy







## 产品系列篇

## Series of Products

### WS系列超重型越野车底盘



WS2600超重型越野车底盘 WS2600 super heavy-duty off-road chassis

- 进口大功率道依茨柴油机，高低双档分动器，动力强劲。
- 进口ZF全自动变速箱，匹配性良好。
- 断开式驱动桥带有轴间和轮间差速器，越野性能优良。
- 超宽断面轮胎和中央充放气技术，通过性优良。
- 高度可调的油气悬架，特别适用于敏感装置的运输。
- 前后多组转向集成技术，机动灵活。
- 在-40℃~50℃条件下工作，环境适应性优良。

- Imported high-power DEUTZ diesel engine uses high-low double gear transfer case which has strong power.
- Imported automatic transmission case of ZF, well matched with the chassis.
- The divided axle has differential gears between the axles and bridges which has great through off-road performance.
- Over-wide cross section tires and central automatic air inflating&deflating system have well traffic ability.
- Varying height hydro pneumatic suspension is especially applied to transport the sensitive installation.
- Front and back multiple steering integrated technology is more mobility and flexibility.
- Works in -40℃ ~ 50℃ condition which has well acclimatization.

尺寸参数	驱动形式	10×8
	总长 (mm)	16350
	总宽 (mm)	3050
	总高 (mm)	2820
轴距	I - II 桥 (mm)	2200
	II - III 桥 (mm)	4650
	III - IV 桥 (mm)	2050
	IV - V 桥 (mm)	2050
质量参数	轮距 (空载) (mm)	2375
	整备质量 (kg)	22500
	最大总质量 (kg)	65000
	最大装载质量 (kg)	42500
性能参数	最高车速 (km/h)	70
	最大爬坡度 (%)	40
	最大驻坡度 (%)	20
	等速百公里平均燃油消耗量 (L/100km)	100
	公路续驶里程 (km)	650
	满载初速30km/h时制动距离 (m)	≤12
	接近角 (°)	18
	离去角 (°)	25
	最小离地间隙 (mm)	400
	最小转弯直径 (m)	30
	最大涉水深度 (m)	1.2
	最大越沟宽度 (m)	2.5
	垂直越障高度 (m)	0.4

SANJIANG-VOLAT SPECIAL VEHICLE CO., LTD.







版权作品，请勿转载